

# WINSOR & NEWTON™

## Artists' Water Colour

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

### Key to Coding

|  |   |
|--|---|
| AA Extremely Permanent                                 | (iv) Fluctuating colour, fades in light, recovers in dark |
| A Permanent  | S Series number   |
| B Moderately Durable                                   | T Transparent   |
| (i) 'A' rated in full strength may fade in thin washes | ST Semi-Transparent                                       |
| (ii) Cannot be relied upon to withstand damp           | O Opaque  |
| (iii) Bleached by acids, acidic atmosphere             | SO Semi-Opaque  |
|  | G Granulating Colour                                      |
|  | St Staining Colour  |

### ASTM

|                               |
|-------------------------------|
| I Permanent for artists' use  |
| II Permanent for artists' use |

Where no ASTM rating is listed, please refer to the Winsor & Newton permanence rating